BIOSPECTRIX SEMI-AUTOMATIC TISSUE CRYOSTAT MICROTOME, MODEL BSRD-2260

ABOUT THE PRODUCT

BSRD-2260 is the new upgraded Cryostat Microtome! This is an indispensable assistant for rapid pathology testing! This cryostat microtome uses touch screen, large screen with all settings at a glance for the operator and is very convenient to use and saves time. It is used in conventional histology and Mohs surgery, produces high quality tissue sections in a fast, simple & efficient way

Freezing chamber interior parts with a fully enclosed design.

- Closed freezer cover plate to ensure that cold in the cooling station is not lost.
- Fully enclosed structure, making cleaning up the sample waste is more simple and convenient.
- Fully enclosed structure, more beautiful and refined.

The vertical cross section of the rack ball is designed

The use of frame cross-ball vertical section design, and the transmission part places in the freezer chamber. while the vertical stroke can be 72mm,specimen horizontal stroke can be 22mm,you can cut more large sample.

The machine adopts frame suspension structure

This machine adopts the frame suspension structure, the chassis shell is only play the role of protection and occlusion which makes the machine more stable to operate even though in ong-distance transport, to make sure 1um is precisely sliced.

CRYOSTAT MICROTOME






9.6 inch touch screen



Quick operation button




Manual handwheel



Liquid collector




Heat Dissipation




Freezing hammer



Specimen chuck



Blade holder



Peltier freezing shelf



UV sterilize

BIOSPECTRIX PVT LTD

info@biospectrix.co

INNOVATION • QUALITY • RELIABLE

★ ★ ★ ★ ★

BioSpectrix

DANFOSS(SECOP)
BRAND COMPRESSOR



- A large-size quick-freezing shelf allows for the preparation of 36 specimens at the same time.
- The specimen retraction function: prevents specimens from accidental blade damage.This function can be turn off.
- The unit can be defrosted manually or by a controlled time setting.
- High quality LCD screen to show all the user specification data.
- High bright and low power LED light, to support the stable bright light.
- UV sterilize function. Equipped with cleaner. Quickly to collect the wastes in the chamber.
- The hand wheel with 16 poison. To be sure the safety.
- The cryostat with two German original Danfoss brand compressors. Special cooling for chamber, for freezing shelf, for knife blade,and the specification.
- Closed freezer cover plate to ensure that cold in the coolingstation isnot lost.
- Fully enclosed structure, making cleaning up the sample waste is more simple and convenient.
- Fully enclosed structure, more beautiful and refined.

Cryostat Microtome Model BSRD-2260	Technical Specifications
Section thickness range:	0.5um–100um adjustable 0.5um–5μm, in 0.5μm increment 5μm–20μm, in 1μm increments 20μm–50μm, in 2μm increments 50μm–100μm, in 5μm increments
Trimming thickness range:	1μm–600μm adjustable 0μm–50μm, in 5μm increments 50μm–100μm, in 10μm increments 100μm–600μm, in 50μm increments
Tissue Retraction function:	0μm–100μm adjustable; in 2μm increment
Peltier cooling working time:	15 minutes
Freezing chamber temperature range:	10℃~–60℃
Speed of fast-forward and back-forward:	0.9mm/s, 0.45mm/s
Specimen head minimum temperature range:	0℃~–60℃
Maximum specimen size:	55mmx80mm
Freeze shelf minimum temperature:	0℃~–55℃
Specimen vertical stroke:	≥65mm
Lowest temperature of Peltier units on freezing shelf:	–60℃
Specimen horizontal stroke:	≥22mm
Power:	500W
Voltage and frequency:	AC220V±10%, 50Hz(Standard); 110V±10%, 60Hz
Net weight:	180Kg
Dimensions(WxDxH):	700MMx760MMx1160MM
Disinfection method:	UV