# BIOSPECTRIX PVT LTD

## HOUSEHOLD FOOD DEHYDRATOR

| | |
|---|---|
| Power: 500W | Voltage: 220-240V/50Hz/60Hz110V/60Hz |
| Temperature: 30-90℃ | Product Size: 35*40*29CM |
| Time Range: 0-24 hours | Drying Tray Size: 28*30CM |
| Noise Level: 45-50dB | Control: Digital Control |
| Features: | · Doublelayerhousing<br>· With an inner LED light<br>· With additional 1pc crumb tray<br>· SUS304 trays<br>· SUS201 housing and liner<br>· Aluminum Handle |
| G.W. :8.8KG | Package Size: 45*39.5*33CM |
| Container Loading | 20GP 436pcs |
| | 40HQ 1013pcs |

6 LAYERS

DOUBLE HOUSING

3KG CAPACITY



BSSS-06H

## HOUSEHOLD FOOD DEHYDRATOR

| | |
|---|---|
| Power: 1000W | Voltage: 220-240V/50Hz/60Hz110V/60Hz |
| Temperature: 30-90℃ | Product Size: 47*57*55CM |
| Time Range: 0-24 hours | Drying Tray Size: 40*38CM |
| Noise Level: 50-55dB | Control: Digital Control |
| Features: | · Double layer housing<br>· With an inner LED light<br>· With additional 1pc crumb tray<br>· SUS304 trays<br>· SUS201 housing and liner<br>· Aluminum Handle |
| G.W. :22.5KG | Package Size: 62.5*52.5*60.5CM |
| Container Loading | 20GP 137pcs |
| | 40HQ 345pcs |

12 LAYERS

DOUBLE HOUSING

12KG CAPACITY



BSSS-12H

## COMMERCIAL FOOD DEHYDRATOR

| | |
|---|---|
| Power: 1500W | Voltage: 220-240V/50Hz/60Hz110V/60Hz |
| Temperature: 30-90℃ | Product Size: 47*57*76CM |
| Time Range: 0-24 hours | Drying Tray Size: 40*38CM |
| Noise Level: 50-55dB | Control: Digital Control |
| Features: | · 2 fans in the compartment<br>· Double layer housing<br>· With an inner LED light<br>· With additional 1pc crumb tray<br>· With 4 wheels<br>· SUS304 trays<br>· SUS201 housing and liner<br>· Aluminum Handle |
| G.W. :26.5KG | Package Size:62.5*52.5*72.5CM |
| Container Loading | 20GP 102pcs |
| | 40HQ 256pcs |

16 LAYERS

DOUBLE HOUSING

16KG CAPACITY



BSSS-16H