BIOSPECTRIX

BSRD-907S-C
BSRD-907S-D

GROSSING TABLE



INTRODUCTION:

Digital pathology workbench provides more efficient and faster working opportunities for pathology. Our main station is specially designed according to the requirements of the construction of anatomical laboratories in medical colleges and hospitals.It provide a clean and safe sampling environment for experimenters. It is a safe and reliable anatomical instrument with beautiful appearance, advanced technology and complete functions.

USAGE SCENARIO:







FEATURE: TOUCH SCREEN MODEL

1: All 304 stainless steel construction.
2: there are built-in lighting on the operation desk.
3: Table height is adjustable from 800mm to 1000mm.
4: The powerful crusher under the pool can crush the broken objects after dissection and discharge them through the drain.
5: There is a hair separator in the pool to prevent hair from entering the drainage pipe and blocking the pipe.
6: Negative pressure ventilation system: the upper ventilation is inhaled downward from the inclined ventilation openings on inner side of the table, and the lower ventilation is inhaled through the openings around the base, which can extract the harmful gas leaked during the dissection process in time (the external ventilation system needs to be connected).
7: Equipped with hot and cold regulator, induction faucet and manual faucet (need to connect water heater).
8: The table is equipped with a sieve isolation plate engraved with a laser scale. The table top can be turned over and detachable.
9: automatic washing device for the table.
10: UV sterilization.

FEATURE: TOUCH SCREEN MODEL

1: All 304 stainless steel construction.
2: there are built-in lighting on the operation desk.
3: Table height is adjustable from 800mm to 1000mm.
4: The powerful crusher under the pool can crush the broken objects after dissection and discharge them through the drain.
5: There is a hair separator in the pool to prevent hair from entering the drainage pipe and blocking the pipe.
6: Negative pressure ventilation system: the upper ventilation is inhaled downward from the inclined ventilation openings on inner side of the table, and the lower ventilation is inhaled through the openings around the base, which can extract the harmful gas leaked during the dissection process in time (the external ventilation system needs to be connected).
7: Equipped with hot and cold regulator, induction faucet and manual faucet (need to connect water heater).
8: The table is equipped with a sieve isolation plate engraved with a laser scale. The table top can be turned over and detachable.
9: automatic washing device for the table.
10: UV sterilization.



SPECIFICATION LIST:

Model No.	BSRD-907S-C
Material	Stainless steel 304
Product Size (mm)	L1500* W800*H2100mm
Table height	800- 1000mm adjustable
Standard parts	Double faucets
Standard parts	3pcs movable board
Standard parts	High pressure shower
Standard parts	LED light
Standard parts	UV disinfection lamp
Standard parts	Magnet tool tray
Standard parts	Automatic washing device for the table
Standard parts	Leakage protector
Pulverizer	Voltage: 220v/50Hz
Pulverizer	Power: 560w
Pulverizer	Horsepower: 1.0hp
Pulverizer	Speed: 4200rpm
Pulverizer	Capacity: 1200ML
Fan specification data	Speed: 500r/min
Fan specification data	Air volume: 30 cubic meters /min
Fan specification data	Noise begets: 39 dB
Fan specification data	Power 54W
Fan specification data	Voltage: 220v/50Hz
Spare parts optional	Exhaust system
Spare parts optional	Keyboard and display screen
Spare parts optional	Keyboard and display screen holder
Spare parts optional	Camera
Spare parts optional	Camera holder
Spare parts optional	Formalin collector and drainer
Spare parts optional	Magnifiers
Spare parts optional	Moveable operate tray
Spare parts optional	Touch screen operation panel
Certification	CE
Customization	YES

Model No.	BSRD-907S-D
Material	Stainless steel 304
Product Size (mm)	L1500* W800*H2100mm
Table height	800mm adjustable
Standard parts	Double faucets
Standard parts	3pcs movable board
Standard parts	High pressure shower
Standard parts	LED light
Standard parts	UV disinfection lamp
Standard parts	Magnet tool tray
Standard parts	Automatic washing device for the table
Standard parts	Leakage protector
Pulverizer	Voltage: 220v/50Hz
Pulverizer	Power: 560w
Pulverizer	Horsepower: 1.0hp
Pulverizer	Speed: 4200rpm
Pulverizer	Capacity: 1200ML
Fan specification data	Speed: 500r/min
Fan specification data	Air volume: 30 cubic meters /min
Fan specification data	Noise begets: 39 dB
Fan specification data	Power 54W
Fan specification data	Voltage: 220v/50Hz
Spare parts optional	Exhaust system
Spare parts optional	Keyboard and display screen
Spare parts optional	Keyboard and display screen holder
Spare parts optional	Camera
Spare parts optional	Camera holder
Spare parts optional	Formalin collector and drainer
Spare parts optional	Magnifiers
Spare parts optional	Moveable operate tray
Spare parts optional	Touch screen operation panel
Certification	CE
Customization	YES