SK-O180
Orbital Shaker



Specification

Model	BSSK-O180
Orbital Diameter	4mm
Max. Load Capacity (With Platform)	2.5kg
Motor Type	Brushless DC motor
Motor Input Power	28W
Motor Output Power	15W
Speed Range	100-800rpm
Speed Display	LCD
Timer Display	LCD
Time Settings Range	1min-19h59min
Voltage	100-240V, 50/60Hz
Power	30W
Permissible Ambient Temperature And Humidity	5-40℃, 80%RH
Protection Class	IP21
Data Connector	RS232
External Size (W×D×H)	450×415×150mm
Shipping Size (W×D×H)	450×450×320mm
N.W./G.W.	8/10kg

BSSK-O180S
Orbital Shaker



Specification

Model	BSSK-O180S
Orbital Diameter	20mm
Max. Load Capacity (With Platform)	2kg
Motor Type	DC motor
Motor Input Power	20W
Motor Output Power	16W
Speed Range	40-200rpm
Speed Display	LED
Timer Display	LED
Time Settings Range	1min-19h59min
Voltage	100-240V, 50/60Hz
Power	20W
Permissible Ambient Temperature And Humidity	5-40℃, 80%RH
Work Plate Size (W×D)	268×268mm
Protection Class	IP21
External Size (W×D×H)	425×360×205mm
Shipping Size (W×D×H)	435×370×230mm
N.W./G.W.	3.82/4.5kg